

netTAP 151

High-end Gateway for Real-Time Ethernet Networks

- 💡 **Bridging between two Real-Time Ethernet networks**
- 💡 **Flexible choice of operating modes Slave/Master or Slave/Slave**
- 💡 **Effortless integration as standard I/O device**
- 💡 **Secure network segregation via internal data buffer**
- 💡 **Fast conversion time less than 10 milliseconds**



EtherNet/IP™

EtherCAT®

Modbus

PROFINET®

ETHERNET POWERLINK

SERCOS
the automation bus

I/O protocol gateway for Real-Time Ethernet conversions

The gateway netTAP 151 transmits IO data bidirectionally between any two industrial Real-Time Ethernet networks. It is the ideal solution for installations with heterogeneous networks or such of the same kind to exchange data across given network boundaries. With more than 25 different combinations of the protocols PROFINET, EtherCAT, EtherNet/IP, POWERLINK, Sercos and Modbus TCP, the device series provides a solution for any conversion.

The integration as simple I/O device into the primary network makes the converter compatible with any common PLC. On the secondary side it works either as I/O device too or controls a subordinate network as a bus master. The length of the I/O data can be scaled to any application and the data in between can be mapped on byte level arbitrarily.

Secure network separation is provided by two Ethernet controllers, each connected to a Dual Ethernet port with integrated switch. That allows realizing star, ring and inline network topologies without further peripherals. Both controllers handle the protocols independent from each other and exchange only the I/O data across a data buffer. An overall data processing time lower than 10 milliseconds is achieved.

The devices can be ordered preloaded with firmware and license or unloaded. Unloaded devices minimize the storage costs. Subsequent loading of a firmware configures these devices for any conversion most flexible. All devices are commissioned and diagnosed network independent over USB.


hilscher
COMPETENCE IN
COMMUNICATION

www.hilscher.com

PRODUCT INFORMATION

TECHNICAL DATA

Technical Data

Operating temperature

-20 °C .. +60 °C

Power supply

+18 ... +30 V / 190 mA @ +24V

Dimensions (L x W x H)

99 x 22,5 x 114,5 mm (without connector)

Weight

121 g

Service Interface

Mini USB

Displays

LED SYS, APL, protocol specific

Configuration

SYCON.net, Windows® 7

Connector

Mini-COMBICON 5-pin

Mounting

DIN-Rail, DIN EN 60715

Note: All technical data may be changed without further notice.

Technical Data

Emission

EN55011 / CISPR 11; Class A

Noise Immunity

EN 61000-6-2

Certification

CE Sign, UL, cUL

Card Slot

SD card

Maximum Cyclic Process Data

	Master	Slave
EtherCAT	9200	512 Bytes I/O-Data
EtherNet/IP	11472	1008 Bytes I/O-Data
POWERLINK		1490 Bytes I/O-Data
PROFINET	11472	2048 Bytes I/O-Data
Sercos	11472	240 Bytes I/O-Data
Modbus TCP	11520	11520 Bytes I/O-Data

The maximum convertible number of I/O data of a protocol combination is determined by the protocol with the lower amount of I/O Data.

Article Overview

NT 151-RE-RE

1722.122 | Loadable device for any Slave/Slave protocol combination (incl. Modbus TCP master)

NT 151-RE-RE/+ML

1722.122/+ML | Loadable device for any Slave/Master or Slave/Slave protocol combination

SD card

1719.003 | SD card to realize the backup and restore functions

NT 151-RE-RE	Network A		EtherCAT	EtherNet/IP	POWERLINK	PROFINET	Sercos
	Network B		Slave	Slave	Slave	Slave	Slave
EtherCAT	Slave		/ECS/ECS	/EIS/ECS	/PLS/ECS	/ECS/PNS	/S3S/ECS
	Master		/ECS/ECM	/EIS/ECM	/PLS/ECM	/PNS/ECM	/S3S/ECM
EtherNet/IP	Slave		/EIS/ECS	/EIS/EIS	/PLS/EIS	/EIS/PNS	/EIS/S3S
	Master		/ECS/EIM	/EIS/EIM	/PLS/EIM	/PNS/EIM	/S3S/EIM
POWERLINK	Slave		/PLS/ECS	/PLS/EIS	/	/PLS/PNS	/PLS/S3S
	Master		/	/	/	/	/
PROFINET	Slave		/ECS/PNS	/EIS/PNS	/PLS/PNS	/PNS/PNS	/S3S/PNS
	Master		/ECS/PNM	/EIS/PNM	/PLS/PNM	/PNS/PNM	/S3S/PNM
Sercos	Slave		/S3S/ECS	/EIS/S3S	/PLS/S3S	/S3S/PNS	/S3S/S3S
	Master		/ECS/S3M	/EIS/S3M	/PLS/S3M	/PNS/S3M	/S3S/S3M
Modbus TCP	Slave / Master		/ECS/OMB	/EIS/OMB	/PLS/OMB	/PNS/OMB	/S3S/OMB

Hilscher News:



HEADQUARTERS

Germany
Hilscher Gesellschaft für Systemautomation mbH
Rheinstraße 15
65795 Hattersheim
Phone: +49 (0) 6190 9907-0
Fax: +49 (0) 6190 9907-50
E-Mail: info@hilscher.com
Web: www.hilscher.com

DISTRIBUTORS

More information at www.hilscher.com

SUBSIDIARIES

China
Hilscher Systemautomation (Shanghai) Co. Ltd.
200010 Shanghai
Phone: +86 (0) 21-6355-5161
E-Mail: info@hilscher.cn

France
Hilscher France S.a.r.l.
69800 Saint Priest
Phone: +33 (0) 4 72 37 98 40
E-Mail: info@hilscher.fr

India
Hilscher India Pvt. Ltd.
Pune, Mumbai
Phone: +91- 8888 750 777
E-Mail: info@hilscher.in

Italy
Hilscher Italia S.r.l.
20090 Vimodrone (MI)
Phone: +39 02 25007068
E-Mail: info@hilscher.it

Japan
Hilscher Japan KK
Tokyo, 160-0022
Phone: +81 (0) 3-5362-0521
E-Mail: info@hilscher.jp

Korea
Hilscher Korea Inc.
Seongnam, Gyeonggi, 463-400
Phone: +82 (0) 31-789-3715
E-Mail: info@hilscher.kr

Switzerland
Hilscher Swiss GmbH
4500 Solothurn
Phone: +41 (0) 32 623 6633
E-Mail: info@hilscher.ch

USA
Hilscher North America, Inc.
Lisle, IL 60532
Phone: +1 630-505-5301
E-Mail: info@hilscher.us